

Y-7 Yoke

AC/DC Electromagnetic Yoke

The Y-7 yoke is a durable, high-strength AC/DC magnetic yoke designed to detect surface and sub-surface indications in the most rugged applications.

Featuring sealed chemical-resistant construction, articulating legs to contour to any part shape and robust strain-relieved twelve-foot cord for field use, the Y-7 is ideal for inspection of welds and other remote testing.

Solid-state controls allow the operator to use AC magnetic fields for surface indications or DC magnetic fields for sub-surface indications to meet all inspection needs.

FEATURES

- Sealed, durable construction
- Chemical and abrasion resistant
- AC and DC operation options for surface and sub-surface inspection
- Exceeds ASTM lifting specifications
- Individual serial number for each yoke

SPECIFICATION COMPLIANCE

- ASME BPVC
- ASTM E709
- ASTM E1444
- ASTM E3024
- ISO 9934-3



APPLICATIONS

Defect location: Surface and subsurface

Ideal for:

- Field testing
- Spot inspections
- In-service inspections
- Demanding environments
- Weld inspection

Defect examples:

- Inclusions
- Seams
- Shrink cracks
- Tears
- Laps
- Welding slag
- Grinding cracks
- Quenching cracks
- Fatigue cracks

PRODUCT PROPERTIES

Weight	8.0 lb / 3.6 kg
Leg Span	2 - 12 in / 5.1 - 30 cm
Cord Length	12 ft / 3.7 m
Duty Cycle	25%, max on time is 90 seconds
Electrical Requirements	115V - 60 Hz: 6.0 A 220/230V - 50/60 Hz: 2.7 A

USE RECOMMENDATIONS

NDT Method	Magnetic Particle Testing
Recommended Accessory	Yoke Test Weight, PN 624115*

* Yokes are compliant based on the lift test required in the specification. The lift test is 10 lbs for AC and a minimum of 30 lbs for DC.